

Listing of Claims:

1. (currently amended) A method comprising:
receiving a broadcast signal containing a plurality of encrypted multimedia channels;
storing said encrypted multimedia channels in a first hard drive partition; and
decrypting one or more of said encrypted multimedia channels stored in the first hard drive partition to generate one or more decrypted multimedia channels; and
storing said decrypted multimedia channels to a second hard drive partition prior to rendering said decrypted multimedia channels on a display.
2. (original) The method as in claim 1 wherein said first hard drive partition is optimized for writing data.
3. (original) The method as in claim 2 wherein for N multimedia channels, writing to said first hard drive partition comprises:
writing a first amount of multimedia data equivalent to a block from each of said 1 through N multimedia channels to each of a first N consecutive blocks in said first hard drive partition, respectively.
4. (currently amended) The method as in claim 3 wherein writing to said first hard drive partition further comprises:
writing a second amount of multimedia data equivalent to a block from each [[osf]] of said 1 through N multimedia channels to each of a second N consecutive

blocks in said first hard drive partition, respectively, said second N consecutive blocks being the next N consecutive blocks following said first N consecutive blocks.

5. (original) The method as in claim 4 further comprising:
selecting a non-consecutive block if one of said first or second N consecutive blocks are unavailable.

6. (original) The method as in claim 5 wherein said non-consecutive block is selected because jumping to said non-consecutive block will require relatively less seek time when compared with all other non-consecutive blocks.

7. (original) The method as in claim 1 wherein said second hard drive partition is optimized for reading data.

8. (original) The method as in claim 1 further comprising:
reading and decoding one or more of said multimedia channels from said second hard drive partition responsive to a user request to view said one or more multimedia channels.

9. (original) The method as in claim 8 wherein decoding comprises MPEG-2 decoding.

BEST AVAILABLE COPY

10. (original) The method as in claim 1 further comprising:
demultiplexing said multimedia channels prior to storing said decrypted multimedia channels to said second hard drive partition.

11. (currently amended) A method for reducing seek time while concurrently writing N multimedia channels to a mass storage device comprising:

writing a first amount of encrypted multimedia data equivalent to a block from each of said 1 through N multimedia channels to each of a first N consecutive blocks on a first hard drive partition on said mass storage device, respectively;

decrypting the multimedia data stored in the first hard drive partition to generate decrypted multimedia data;

writing the decrypted multimedia data equivalent to a block from each of said 1 through N multimedia channels to each of a second N consecutive blocks in a second hard drive partition on said mass storage device prior to rendering said decrypted multimedia data on a display.

12. (canceled)

13. (currently amended) The method as in claim ~~[[12]]~~ 11 further comprising:
selecting a non-consecutive block if one of said first or second N consecutive blocks are unavailable.

BEST AVAILABLE COPY

14. (original) The method as in claim 13 wherein said non-consecutive block is selected because jumping to said non-consecutive block will require relatively less seek time when compared with all other non-consecutive blocks.

15. (original) The method as in claim 11 further comprising:
pre-allocating metadata identifying each of said N multimedia channels stored on said mass storage device before writing said first amount of multimedia data for each of said 1 through N multimedia channels.

16. (original) The method as in claim 15 wherein pre-allocating metadata comprises:

estimating an amount of storage space which programs from each of said multimedia channels will consume; and

pre-allocating an amount of metadata sufficient to identify said amount of storage space.

17. (original) The method as in claim 15 wherein said metadata comprises an I-node and one or more indirect blocks.

18. (original) A method for storing data on a mass storage in a format in which it can be deleted efficiently:

pre-allocating metadata to consecutive blocks on said mass storage device before writing said data.

BEST AVAILABLE COPY

19. (original) The method as in claim 18 wherein pre-allocating metadata comprises:

estimating an amount of storage space which said data will occupy; and
pre-allocating an amount of metadata sufficient to identify said amount of storage space.

20. (original) The method as in claim 18 wherein said metadata comprises an I-node and one or more indirect blocks.

21. (original) The method as in claim 20 wherein said metadata further comprises a doubly-indirect block.

22. (original) A system for efficiently storing multimedia content from N multimedia channels comprising:

a block allocation module to interleave multimedia content from each of said multimedia channels in successive blocks on a mass storage device.

23. (original) The system as in claim 22 further comprising:
pre-allocation logic for pre-allocating metadata identifying said multimedia content before said multimedia content is stored on said mass storage device.

BEST AVAILABLE COPY

24. (original) The system as in claim 23 wherein pre-allocating metadata comprises:

estimating an amount of storage space which said multimedia content will occupy; and

pre-allocating an amount of metadata sufficient to identify said amount of storage space.

25. (original) The method as in claim 23 wherein said metadata comprises an I-node and one or more indirect blocks.

26. (currently amended) An article of manufacture having program code stored thereon which, when executed by a machine, cause said machine to perform the operations of:

receiving a broadcast signal containing a plurality of encrypted multimedia channels;

storing said encrypted multimedia channels in a first hard drive partition; and

decrypting one or more of said encrypted multimedia channels stored in the first hard drive partition to generate one or more decrypted multimedia channels; and

storing said decrypted multimedia channels to a second hard drive partition prior to rendering said decrypted multimedia channels on a display.

27. (original) The article of manufacture as in claim 26 wherein said first hard drive partition is optimized for writing data.

BEST AVAILABLE COPY

28. (original) The article of manufacture as in claim 27 wherein for N multimedia channels, writing to said first hard drive partition comprises:

writing a first amount of multimedia data equivalent to a block from each of said 1 through N multimedia channels to each of a first N consecutive blocks in said first hard drive partition, respectively.

29. (original) The article of manufacture as in claim 28 wherein writing to said first hard drive partition further comprises:

writing a second amount of multimedia data equivalent to a block from each of said 1 through N multimedia channels to each of a second N consecutive blocks in said first hard drive partition, respectively, said second N consecutive blocks being the next N consecutive blocks following said first N consecutive blocks.

30. (original) The article of manufacture as in claim 29 including program code to cause said machine to perform the additional operation of:

selecting a non-consecutive block if one of said first or second N consecutive blocks are unavailable.

31. (original) The article of manufacture as in claim 30 wherein said non-consecutive block is selected because jumping to said non-consecutive block will require relatively less seek time when compared with all other non-consecutive blocks.

BEST AVAILABLE COPY

32. (currently amended) The article of manufacture as in claim [[1]] 26 wherein said second hard drive partition is optimized for reading data.

33. (original) The article of manufacture as in claim 26 including program code to cause said machine to perform the additional operation of:

reading and decoding one or more of said multimedia channels from said second hard drive partition responsive to a user request to view said one or more multimedia channels.

34. (original) The article of manufacture as in claim 33 wherein decoding comprises MPEG-2 decoding.

35. (original) The article of manufacture as in claim 26 including program code to cause said machine to perform the additional operations of:

demultiplexing said multimedia channels prior to storing said decrypted multimedia channels to said second hard drive partition.

36. (currently amended) The method as in claim [[1]] 26 wherein said first hard drive partition is on a first hard drive and said second hard drive partition is on a second hard drive.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.